

Consent For Operation (CFO-Air.Water)

ant No. AW-332708

Valid upto: 30/06/2023 Industry Colour: RED Industry Scale: LARGE

Application Type: CfO-

(This document contains 5 pages including annexure & excluding additional

Combined Consent Order No. AW-332708

PCB ID:

12690

Date: 08/08/2022

Combined consent for discharge of effluents under the Water (Prevention and Control of Pollution) Act, 1974 and emission under the Air (Prevention and Control of Pollution) Act, 1981

1. Application filed by the applicant/organization on 09/12/2021

2.Inspection of the

on 08/12/2021

Karnataka State Pollution Control Board Parisara Bhavana, No.49, Church

Street, Bengaluru-560001

email id: ho@kspcb.gov.in

Fax:080-25586321

Tele: 080-25589112/3, 25581383

Industry/organization/by RO,

3. Proceedings of the ECM dated 21/06/2022

held on 16/06/2022

Consent is hereby granted to the Occupier under Section 25(4) of the Water (Prevention & Control of Pollution) Act, 1974 (herein referred to as the Water Act) & Section 21 of Air (Prevention & Control of Pollution) Act, 1981, (herein referred to as the Air Act) and the Rules and Orders made there under and authorized the Occupier to operate /carryout industry/activity & to make discharge of the effluents & emissions confirming to the stipulated standards from the premises mentioned below and subject to the terms and conditions as detailed in the Schedule Annexed to this order.

Location:

Name of the Industry: Shri Hiranyakeshi Sahakari Sakkare Karkhane Niyamit

Address:

Sy.No.317/1A, 318, 319/1 & 2, 320, 322/1 & 2, 323/1+2A,1+2B,, Sankeshwar village, Hukkeri Taluk,

Belgaum District

Industrial Area:

Not In I.A,

Sankeshwar,

Taluk:

Hukkeri.

District: Chikkodi

CONDITIONS:

a) Discharge of effluents under the Water Act:

	Water Code	WC(KLD)	WWG(KLD)	Remark
1	Boiler Feed	200.000	20.000	The boiler blow down shall be treated in ETP and the treated effluent shall be used for on land irrigation within the premises.
2	Cooling Water	624.000	32.000	The cooling tower blow down shall be treated in ETI and the treated effluent shall be used for on land irrigation within the premises.
3	D.M Water Plant	200.000	40.000	The DM Plant reject shall be treated in ETP and the treated effluent shall be used for on land irrigation within the premises.
4	Domestic Purpose	100.000	95.000	Sewage shall be disposed to individual septic tank and soak pits designed as per IS 2470 -1985 (Part -1 & 2). There shall not be any overflow from the septic tank / soak pits
5	Manufacturing Processes	546.000	540.000	Distillery -The spent lees & condensates from the distillery - about 108 KLD shall be treated in the existing ETP till installation of new CPU of 1000 KLD. The spent wash of 432 KLI shall be collected in lined impervious lagoons (3 Nos and used for surface composting in an area of 6 acres
6	Manufacturing Processes	350.000	708,000	Water used for sugar plant. The effluent from sugar plant, the boiler blow down shall be treated in ETP and the treated effluent shall be used for on land irrigation within the premises.

SHRI H.S.S.K.N. SKV Inward No. 525

9 AUG 2022

Dept. Tennee M.D. Sign.

b) Discharge of Air emissions under the Air Act from the following stacks etc.

Sl. No. Description of chimney/outlet

Limits specified refer schedule

The details of Sources, control equipments and its specification, type of fuel constituents to be controlled in emissions etc, are detailed in Annexure-II.



Consent For Operation (CFO-Air.Water)

Consent No. AW-332708 alld upto: 30/06/2023

Karnataka State Pollution Control Board Parisara Bhavana, No.49, Church Street, Bengaluru-560001 Tele: 080-25589112/3, 25581383 Fax:080-25586321 email id: ho@kspcb.gov.in

Industry Colour: RED

Application Type: CfO-

Industry Scale: LARGE

This document contains

5 pages including annexure & excluding additional

The consent for operation is granted considering the following activities/Products;

Product Name	Applied Oty	Unit
cogeneration	52,0000	Mega W
distillery	54,0000	Kilo Litres/D
sugar cane crushing	8000,0000	Tonnes Crushed Per Da

This consent is valid for the period from

01/07/2021

To,

Shri Hiranyakeshi Sahakari Sakkare Karkhane Niyamit

COPY TO:

The Environmental Officer, KSPCB, Regional Office Belgaum (Chikkodi) for information and necessary action.

- 2. Master Register.
- Case file.

Consent Fee paid

: Rs. 4000000

SCHEDULE

TERMS AND CONDITIONS

TREATMENT AND DISPOSAL OF EFFLUENTS UNDER THE WATER ACT.

- The discharge from the premises of the occupier shall pass through the terminal manhole/manholes where from the Board shall be free to collect samples in accordance with the provisions of the Act/Rules made there under.
- 2(a). The sewage/domestic effluent shall be treated in septic tank and with soak pit. No overflow from the soak pit is allowed. The septic tank and soak pit shall be as per IS 2470 Part-I & Part-II.
- 2(b). The treated sewage effluent discharged shall conform to the standards specified in Annexure-I.
- 3(a). The trade effluent generated in the industry shall be treated in the ETP and treated effluent shall confirm to the standards stipulated by the Board in Annexure-I
- 3(b). The trade effluent shall be handed over to CETP and maintain logbook of effluent generated & sent every day.
- 4. The applicant shall install flow measuring/recording devices to record the discharge quantity and maintain the
- 5. The applicant shall not change or alter either the quality or the quantity or the place of discharge or temperature or the point of discharge without the previous consent/ permission of the Board.
- 6. The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises. Storm water shall not be allowed to mix with the effluents on the upstream of the terminal manhole where the flow measuring devices are installed.
- 7. The daily quantity of domestic effluent and trade effluent from the industry shall not exceed the limits as indicated in this consent order:
- 8. The applicant shall discharge the effluents only to the place mentioned in the Consent order and discharge of treated/untreated outside the premises is not permitted.



Consent For Operation (CFO-Air.Water)

Consent No. AW-33270 Valid upto: 30/08/2023

Industry Colour: RED

Industry Sosie: LARGE

Application Type: CfO-

(This document contains

5 pages including annexure & excluding additional

B. EMISSIONS:

1. The discharge of emissions from the premises of the applicant shall pass through the air pollution control equipment and discharged through stacks/chimneys mentioned in Annexure-II where from the Board shall be free to collect the samples at any time in accordance with the provisions of the Act and Rules made there under. The tolerance limits of the constituents forming the emissions in each of the stacks shall not exceed the limits laid down in Annexure-II.

Karnataka State Pollution Control Board

Parisara Bhavana, No.49, Churci

Street, Bengaluru-\$60001 080-25589112/3, 25581383

email id: ho@kspeb.gov.in

Fax:080-25586321

- 2. The applicant shall provide port holes for sampling of emission, access platforms for carrying out stack sampling, electrical points and all other necessary arrangements including ladder as indicated in Annexure-II.
- 3. The applicant shall upgrade/modify/replace the control equipment with prior permission of the Board.

C.MONITORING & REPORTING:

- 1. The applicant shall get the samples of effluents & emissions collected and get them analyzed once a month/either by in house monitoring laboratory or through EP approved laboratories for the parameters as Indicated in Annexure I & II.
- 2. The applicant shall maintain log books to reflect the working condition of pollution control systems and also self monitoring results and keep it open for inspection.

D. SOLID WASTE (OTHER THAN HAZARDOUS WASTE) DISPOSAL:

- 1. The applicant shall segregate solid waste from Hazardous Waste, Municipal Solid Waste and store it properly till treatment/disposal without causing pollution to the surrounding Environment.
- 2. The solid waste generated shall be handled & disposed by scientific method without causing eye sore to the general public and to the surrounding environment.

E. NOISE POLLUTION CONTROL:

The applicant shall ensure that the ambient noise levels within its premises during construction and during operational period shall not exceed w.r.t Area/Zone as per Noise Pollution (Regulation and Control) Rules, 2000 as mentioned below:-

- a) In Industrial Area 75 dB(A) Leq during day time and 70 dB(A) Leq during night time.
- b) In Commercial Area 65 dB(A) Leq during day time and 55 dB(A) Leq during night time.
- c) In Residential Area 55 dB(A) Leq during day time and 45 dB(A) Leq during night time.
- d) In Silence Zone 50 dB(A) Leq during day time and 40 dB(A) Leq during night time.
- Note: * Day time shall mean 6 am to 10 pm and Night time shall mean 10 pm to 6 am.
 - dB(A) Leq denotes the time weighted average of the level of sound in decibels on scale A which is relatable to human hearing.
 - A "decibel" is a unit in which noise is measured.
 - "A", in dB(A) Leq, denotes the frequency weighting in the measurement of noise and corresponds to frequency response characteristics of the human ear.
 - * Leq: It is an energy mean of the noise level over a specified period.

F. HAZARDOUS AND OTHER WASTES (MANAGEMENT & TRANSBOUDARY MOVEMENT) Rules 2016:

The applicant shall comply with the provisions of the Hazardous and other Wastes (Management & Transboundry Movement) Rules 2016.



Consent For Operation (CFO-Air.Water)

Consent No. AW-332708 Valid upto: 30/06/2023

Industry Colour: RED

Industry Scale: LARGE

Parisara Bhavana, No.49, Church Street, Bengaluru-56001 Tele: 080-25589112/3, 25581383 Fax: 080-25586321 email id: ho@kspcb.gov.in

Karnataka State Pollution Control Board

Application Type: CfO-

(This document contains

5 pages including annexure & excluding additional

G. GENERAL CONDITIONS:

- 1. The applicant shall not allow the discharge from the other premises to mix with the discharge from his premises.
- The applicant shall promptly comply with all orders and instructions issued by the Board from time to time or any other officers of the Board duly authorized in this behalf.
- The applicant shall set-up Environmental Cell comprising of qualified and competent personnel for complying
 with the conditions specified.
- 4. The Board reserves the right to review, impose additional conditions, revoke, change or alter terms and conditions of this consent.
- 5. The applicant shall forthwith keep the Board informed of any accidental discharge of emissions/effluents into the atmosphere in excess of the standards laid down by the Board. The applicant shall also take corrective steps to mitigate the impact.
- 6. The applicant shall provide alternate power supply sufficient to operate all Pollution control equipments.
- 7. The entire premises shall always be kept clean. The effluent holding area, inspection chambers, outlets, flow measuring points should made easily approachable.
- 8. The applicant shall display the consent granted in a prominent place for perusal of the inspecting officers of the Board.
- 9. The applicant his heirs, legal representatives or assignee shall have no claims what so ever to the continuation or renewal of this consent after expiry of the validity of consent.
- 10. The applicant shall make an application for consent for subsequent period at least 45 days before expiry of this consent.
- 11. The applicant shall develop and maintain adequate green belt all around the periphery.
- 12. The applicant shall provide rain water harvesting system and shall provide proper storm water management system.
- 13. This consent is issued without prejudice to any Court Cases pending in any Hon'ble Court
- 14. The applicant shall furnish the Environmental statement for every financial year ending with 31st March in Form-V as per Environment (Protection) Rules, 1986. The statement shall be furnished before the end of September.
- 15. The applicant shall display flow diagram of the pollution control system near the pollution contol system/s.

NOTE

The Conditions A(2b & 3b) mentioned in the schedule are not applicable.

Additional Conditions:

- 1. The occupier shall comply with all the Additional Conditions and Standards stipulated in Annexures-I, A, B & C attached with this consent order.
- 2. This consent order contains 16 pages including Additional Conditions and Annexures.
- 3. The products with quantities, water consumption, waste water generation, mode of disposal with standards, air pollution sources with control measures

mentioned in Additional Conditions attached with this order shall be considered and to be complied by the industry,



Renewal

Consent For Operation (CFO-Air.Water)

Consent No. AW-332708 Valid upto: 30/06/2023

Industry Colour: RED

Industry Scale: LARGE

Application Type: CfO-

Chi m.N		KVA	Minimum chimney height to be provided above ground level (in Mts)	s including annexure & Constituents to be controlled in the emission	Tolerance limits mg/NM3	Fuel	Control	Date of which air pollution control equipments shall be provided to achieve the stipulated tolerance limits and chimney heights conforming to
1	D.G. Sets	1975 KVA	30	PM,SO2,NOx,CO,	75,-,710,150,100	DIE	AEC,PRT	stipulated heights. At all times
2	Boiler	Distillery 1 x 20	47	PM,SO2,NOx,CO, NMHC	150,-,-,-	BAG	FIL,PRT	At all times
3	Boiler	Cogen Boiler 2 x 100 TPH		PM,SO2,NOx,CO, NMHC	150,-,-,-	BAG	ESP,PRT	At all times
4	D.G. Sets	750KVA x 1		PM,SO2,NOx,CO,		DIE	AEC	At all times

Karnataka State Pollution Control Board Parisara Bhavana, No. 49, Church

Street, Bengaluru-560001

Fax:080-25586321 email id: ho@kspcb.gov.in

Tele: 080-25589112/3, 25581383

Note:

AEC,PRT : Accoustic Enclosures

FIL.PRT : Bag Filte ESP,PRT : E.S.P

: Accoustic Enclosures AFC

The Noise levels within the premises shall not exceed 75 dB (A) leq during day time and 70 dB(A) leq during night

respectively.

2. The DG set shall be provided with acoustic measures as per SI.No.94 in Schedule-I of Environment

(Protection)Rules. There shall be no smell or odour nuisance from the industry.

LOCATION OF SAMPLING PORTHOLES, PLATFORMS, ELECTRICAL OUTLET.

Location of Portholes and approach platform;

Portholes shall be provided for all chimneys, stacks and other sources of emission. These shall serve as the sampling points. The sampling point should be located at a distance equal to atleast eight times the stack or duct diameters downstream and two diameters upstream from source of low disturbance such as a Bend, Expansion, Construction Valve, Fitting or Visible Flame for rectangular stacks, the equivalent diameter can be calculated from the following equation.

- 2. The diameter of the sampling port should not be less than 100 mm dia". Arrangements should be made so that the porthole is closed firmly during the non sampling period
- 3. An easily accessible platform to accommodate 3 to 4 persons to conveniently monitor the stack emission from the portholes shall be provided. Arrangements for an Electric Outlet Point of 230 V 15 A with suitable switch control and 3 Pin Point shall be provided at the Porthole location.
- The ladder shall be provided with adequate safety features so as to approach the monitoring location with ease.

Signature Not Verified Digitally signed by Date: 2022.08.08 13:42:40 +05130 and on half of the Karnataka State Pollution Control Board time